## Formation and Characterization of Al<sub>x</sub>Mo<sub>1-x</sub>/n-InP Alloy Electrode System for Realization of Thermally Stable Ohmic Contacts

Robina Atsuchi, Mayumi B. Takeyama, Atsushi Noya, Tamotsu Hashizume\* and Hideki Hasegawa\*

Department of Electrical and Electronic Engineering, Faculty of Engineering, Kitami Institute of Technology, Kitami 090-8507, Japan

\*Research Center for Interface Quantum Electronics and Graduate School of Electronics and Information Engineering, Hokkaido University, Sapporo 060-8628, Japan E-mail: <a href="mailto:mami@elec.kitami-it.ac.jp">mami@elec.kitami-it.ac.jp</a>, Phone: +81-157-26-9288, Fax: +81-157-25-1087

## **Abstract**

A novel metallization scheme of  $Al_{0.9}Mo_{0.1}/n$ -InP is demonstrated to serve as a thermally stable ohmic contact. Ohmic behavior was obtained in the as-deposited contact, and the linear I-V characteristic was maintained after annealing at 500 °C for 20s. It was found that the ohmic behavior was related to the diffusion of Al with Mo into the InP substrate, forming Al-Mo-P compounds at the interface. The initially formed interfacial products scarcely change upon annealing. This is considered to be the main reason for the stable electrical properties in the  $Al_{0.9}Mo_{0.1}/InP$  contact obtained in this study.